


Submitted Model No.:	
Specific Features:	



▲ Designate proper finish suffix

Hand Shower Spray Pattern



Sprav



Massage





w/ Massage



Sprav



♦ Your Delta Faucet hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.



see what Delta can do

HAND SHOWER

- 5-Spray Setting Hand Shower
- Water efficient Hand Shower

FEATURES:

■ Touch-Clean® Nozzles

STANDARD SPECIFICATIONS:

- Hand shower dial changes spray modes, including a pause feature - a non-positive shut-off.
- Standard 1/2" pipe fitting
- ADA compliant hand shower when installed per accessibility quidelines of the act
- Maximum 1.5 gpm @ 80 psi, 5.7L/min @ 550 kPa

WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH

- ASME A112.18.1 / CSA B125.1 ◆
- ASME A112.18.3 ◆
- EPA WaterSense®