

# Provided in the control of the contr

# **Features**

- Acts as an auxiliary interface for DTV Mode<sup>™</sup> or DTV Prompt<sup>®</sup> two-outlet digital interface.
- Provides simple on/off actuation of shower outlets.
- Sleek, minimalist design.

# Installation

- Wall-mount.
- Intended for outside of showering space.

# **Required Products/Accessories**

K-527 digital shower interface, portrait setting K-528-PM Two-port digital thermostatic valve

OI

K-29200 Wall-mount bath filler digital interface K-528-PM Two-port digital thermostatic valve

or

K-29201 Surface-mount bath/shower digital interface K-528-PM Two-port digital thermostatic valve

or

K-29202 Dual-outlet shower digital interface K-528-PM Two-port digital thermostatic valve

or

K-29204 Deck-mount bath filler digital interface K-528-PM Two-port digital thermostatic valve

or

K-29205 Deck-mount bath/shower digital interface K-528-PM Two-port digital thermostatic valve

# **Recommended Products/Accessories**

K-23723 Faucet cleaner

# **Included Components**

Additional Components: Mounting hardware



# Codes/Standards

UL 1951 CSA C22.2 No. 14 CSA C22.2 No. 68

# KOHLER® Electronic Faucets, Valves, and Controls Five-Year Limited Warranty

See website for detailed warranty information.

# **Available Colors/Finishes**


Color tiles intended for reference only.


**Color Code Description** 

CP Polished Chrome









# **Technical Information**

All product dimensions are nominal.

Drain included: No

Max. Ambient temp: 104°F (40°C) Min. Operating temp: 86°F (30°C) Max. Operating temp: 120°F (48.9°C)

Max. Relative 100%

humidity condensing:

#### **Notes**

Install this product according to the installation instructions.

