

### Features

- Lever handle style option.
- 7-1/2" (191 mm) gooseneck non-diverter spout with slip-fit connection.

### Material

- Brass construction.
- KOHLER finishes resist corrosion and tarnishing.

### Installation

Deck-mount.

### **Required Products/Accessories**

K-300-K High Flow Bath Valve

- or
- K-300-KR High Flow Valve w/ Rigid Connections or

K-301-K 3/4" High-Flow Bath Valve

## Recommended Products/Accessories

K-23723 Faucet cleaner

### **Optional Products/Accessories**

58598 Deep Rough-in Kit



**Purist**®

K-T14428-4

**Bath Faucet Trim** 

ADA CSA B651 OBC

Codes/Standards ASME A112.18.1/CSA B125.1 ADA ICC/ANSI A117.1 CSA B651 OBC

# KOHLER<sup>®</sup> Faucet Lifetime Limited Warranty

See website for detailed warranty information.

### **Available Colors/Finishes**

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	SN	Vibrant® Polished Nickel
	BGD	Vibrant® Moderne Brushed Gold
	G	Brushed Chrome
	BN	Vibrant® Brushed Nickel
	BV	Vibrant® Brushed Bronze
	BL	Matte Black
	RGD	Vibrant Rose Gold



#### **Purist**® **KOHLER**, Faucets **Bath Faucet Trim** K-T14428-4 —7-1/2" (191 mm)—+ 2-1/2" 1-3/8" (64 mm) (35 mm) 2-5/8" (67 mm) 11-3/8" (289 mm) 7-3/4" (197 mm) Ø 2-1/2" 4-3/4" (64 mm) (121 mm) 1/4" (6 mm) -2-1/8" (54 mm) 1/4" (6 mm) -2-1/8" (54 mm) Max Rim or 1-1/4" (32 mm) Max Rough Deck Deck Mount Max Finished Deck Ø 7/8" Ø 1-5/16" (22 mm) (33 mm) 3/4" ID -8" (203 mm) Min-

Rim or Deck-Mount Installation Rough + Finished Deck-Mount Installation

### **Technical Information**

All product dimensions are nominal.

### Notes

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

